## Amendments to the Claims:

Please amend the claims to read, as follows:

- 1.6. (canceled)
- 7. (currently amended) A [[The]] method of Claim 1, controlling a vehicle interior heating and air conditioning system equipped with actuators, comprising the acts of:

detecting interior conditions with an interior sensing system;
automatically detecting seat occupancy with an object recognition system
on the basis of data received from the interior sensing system; and

adjusting automatically the heating and air conditioning system actuators
as a function of seat occupancy to maintain desired interior conditions at at least
one of a plurality of seats within the vehicle interior.

wherein

in the step of detecting seat occupancy, a head position is calculated by the object recognition system for at least one occupant, and

in the adjusting step, an optimized setting of the heating and air conditioning system for each detected occupant is automatically performed by actuators as a function of seat occupancy and head position.

8. (currently amended) The method of Claim 7 [[2]], wherein

in the adjusting step, if one of the plurality of seats is unoccupied by a

passenger, the actuators of the heating and air conditioning system are operated

so that one of a fan intensity and an air distribution in the direction of the unoccupied one of the plurality of seats is adjusted.

in the step of detecting seat occupancy, a head position is calculated by the object recognition system for at least one occupant, and

in the adjusting step, an optimized setting of the heating and air conditioning system for each detected occupant is automatically performed by actuators as a function of seat occupancy and head position.

9. (currently amended) The method of Claim 7 [[3]], wherein

in the adjusting step, the actuators of the heating and air conditioning

system are operated so that a temperature at an unoccupied one of the plurality

of seats is adjusted toward the desired interior conditions.

in the step of detecting seat occupancy, a head position is calculated by the object recognition system for at least one occupant, and

in the adjusting step, an optimized setting of the heating and air conditioning system for each detected occupant is automatically performed by actuators as a function of seat occupancy and head position.

10. (currently amended) The method of Claim 8 [[4]], wherein

in the adjusting step, the actuators of the heating and air conditioning

system are operated so that a temperature in an area of an unoccupied one of the plurality of seats is adjusted toward the desired interior conditions.

in the step of detecting seat occupancy, a head position is calculated by the object recognition system for at least one occupant, and

in the adjusting step, an optimized setting of the heating and air conditioning system for each detected occupant is automatically performed by actuators as a function of sout occupancy and head position.

11. (currently amended) The method of Claim 7 [[5]], wherein
in the adjusting step, the actuators of the heating and air conditioning
system are operated during interior cooling so that a temperature at an
unoccupied one of the plurality of seats is permitted to increase to reduce heating
and air conditioning system energy usage.

in the step of detecting seat occupancy, a head position is calculated by the object recognition system for at least one occupant, and

in the adjusting step, an optimized setting of the heating and air conditioning system for each detected occupant is automatically performed by actuators as a function of seat-occupancy and head position.

12. (currently amended) The method of Claim 8 [[6]], wherein
in the adjusting step, the actuators of the heating and air conditioning
system are operated during interior cooling so that a temperature at an
unoccupied one of the plurality of seats is permitted to increase to reduce heating
and air conditioning system energy usage.

in the step of detecting seat occupancy, a-head position is calculated by the object recognition system for at least one occupant, and in the adjusting step, an optimized setting of the heating and air conditioning system for each detected occupant is automatically performed by actuators as a function of seat-occupancy and head-position.